

#### SAFETY DATA SHEET

This Safety Data Sheet is provided in compliance with the EC Regulations 1907/2006, 1272/2008, 2015/830 and 2020/878

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

- Product Name: Weldtite Citrus Degreaser spray

- Product Part Number: 03002 (400ml)

- UFI: 6A4W-22XU-9405-1VDV

1.2 Relevant identified uses of the substance or mixture and uses advised against

- Use of the substance/mixture: Cleaning agent

1.3 Details of the supplier of the safety data sheet

- Name of Supplier: Weldtite Products Ltd

- Address of Supplier: Unit 9, Harrier Road, Humber Bridge Industrial Estate,

Barton upon Humber, North Licolnshire, DN18 5RP UK

- Telephone: +44 (0)1652 660000

- Email: Sales@weldtite.co.uk Web: www.weldtite.cc

EU Authorised Representative: Comply Express Unipessoal Limitada, StartUp Madeira,

EV141, Campus daPenteada, 9020 105 Funchal, Portugal

Tel: (+351) 300509778

Email: info@complyexpress.com

1.4 Emergency telephone number

- Emergency Telephone: UK: Contact the NHS Information Service (dial 111, 24hr service)

- Company: \*\*44 (0)1652 660000 (08.30 to16:30 Mon - Fri)

### **SECTION 2: Hazards identification**

- 2.1 Classification of the substance or mixture
  - CLP: STOT SE 3, Flam. Aerosol 1, Press. Gas, Skin Irrit. 2, Eye Irrit. 2, Aquatic Chronic 2, Asp. Tox. 1
- 2.2 Label elements







- Signal Word: Danger

- Contains: Hydrocarbons, C6-7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Propan-2-ol

Hazard statements

H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

H336 - May cause drowsiness or dizziness.

H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements

Datasheet Number: 03002 - v3.0.0

Created: 20 Sep 2024. Revised:: 20 Sep 2024.

### **SECTION 2:** Hazards identification (....)

P102 - Keep out of reach of children.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P271 - Use only outdoors or in a well-ventilated area.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F.

#### Supplemental Hazard information (EU)

EUH208 - Contains d-Limonene (5989-27-5). May produce an allergic reaction.

Composition information in accordance with EC Regulation 648/2004 of the European Parliament and of the Council of 31st March 2004 on detergents: Aliphatic hydrocarbons 15 < 30% (propellant), aliphatic hydrocarbons > 30%, perfumes d-Llimonene

#### 2.3 Other hazards

- Not a PBT according to REACH Annex XIII
- The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Common Delegated Regulation (EU) 2017/2010 or Common Regulation (EU) 2018/605 at a concentration equal or greater than 0.1%.

# SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

CAS Number:

EC Number: 921-024-6 Concentration: 25-45%

Categories: Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2

REACH Registration Number: 01-2119475514-35

H Statements: H225, H304, H315, H336, H411

propan-2-ol

CAS Number: 67-63-0 EC Number: 200-661-7 Concentration: 20-35%

Categories: Flam. Liq. 2, Eye Irrit. 2, STOT SE 3

H Statements: H225;H336;H319 Index No.: 603-117-00-0

Petroleum gases, liquefied

CAS Number: 68476-85-7
EC Number: 270-704-2
Concentration: 10-30%

Categories: Flam. Gas 2, Press. Gas

H Statements: H220;H280 Index No.: 649-202-00-6

Hydrocarbons, C6, Isoalkanes, <5% N-Hexane

CAS Number: 64742-49-0
EC Number: 931-254-9
Concentration: 10-25%

Categories: Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2

REACH Registration Number: 01-2119484651-34

Datasheet Number: 03002 - v3.0.0

Created: 20 Sep 2024. Revised:: 20 Sep 2024.

## SECTION 3: Composition/information on ingredients (....)

H Statements: H225, H304, H315, H336, H411

(R)-p-mentha-1,8-diene; d-limonene

CAS Number: 5989-27-5 EC Number: 227-813-5 Concentration: <1%

Categories: Flam. Liq. 3; Skin Irrit. 2; Skin Sens. 1; Aquatic Acute 1; Aquatic Chronic 1

H Statements: H226,H315,H317,H410,H400

Index No.: 601-096-00-2

#### SECTION 4: First aid measures

- 4.1 Description of first aid measures
  - In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible)
  - Contaminated clothing should be laundered before reuse

#### Contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention. When in doubt or symptoms persist, seek medical attention

#### Contact with skin

Wash affected area with plenty of water

If skin irritation occurs: Get medical advice/attention.

#### Ingestion

Rinse mouth with water (only if the person is conscious)

Do not induce vomiting Seek medical advice

#### Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

When in doubt or symptoms persist, seek medical attention

- 4.2 Most important symptoms and effects, both acute and delayed
  - Causes dizziness, confusion, headache or stupor
  - May cause irritation
- 4.3 Indication of any immediate medical attention and special treatment needed
  - Treat symptomatically

# **SECTION 5: Firefighting measures**

- 5.1 Extinguishing media
  - In case of fire use foam, carbon dioxide or dry agent
  - Do not use water jets
- 5.2 Special hazards arising from the substance or mixture
  - Smoke from fires is toxic. Take precautions to protect personnel from exposure
  - Decomposition products may include carbon oxides
  - Inform Fire Brigade of potential danger of exploding and rocketing cylinders
- 5.3 Advice for firefighters
  - Wear Breathing Apparatus
  - Ventilate area
  - Wear full protective clothing including chemical protection suit

Datasheet Number: 03002 - v3.0.0

Created: 20 Sep 2024. Revised:: 20 Sep 2024.

### **SECTION 5:** Firefighting measures (....)

- Keep container(s) exposed to fire cool, by spraying with water
- Prevent run off water from entering drains if possible

#### SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures
  - Eliminate all ignition sources.
  - Ensure adequate ventilation
  - Wear protective clothing as per section 8
- 6.2 Environmental precautions
  - Do not allow to enter public sewers and watercourses
  - Use appropriate containment to avoid environmental contamination
  - If contamination of drainage systems or water courses is unavoidable, immediately inform appropriate authorities
- 6.3 Methods and material for containment and cleaning up
  - Absorb spillage in suitable inert material
  - Remove contaminated material to safe location for subsequent disposal
  - Do not absorb spillage in sawdust or other combustible material
  - Seek expert advice for removal and disposal of all contaminated materials and wastes
- 6.4 Reference to other sections
  - See Section 8 + 13

## SECTION 7: Handling and storage

- 7.1 Precautions for safe handling
  - Use only in well ventilated areas
  - Keep away from heat and sources of ignition
  - When using do not eat, drink or smoke
  - Wash hands thoroughly after using this substance
- 7.2 Conditions for safe storage, including any incompatibilities
  - Keep only in the original container in a cool, well ventilated place away from heat
  - Keep container tightly closed
  - Store locked up.
  - Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F.
- 7.3 Specific end use(s)
  - See Section 1.2

### **SECTION 8:** Exposure controls/personal protection

### 8.1 Control parameters

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

DNEL (Consumer; dermal, long term systemic effects): 699 mg/kg bw/day DNEL (Consumer; inhalational, long term systemic effects): 608 mg/m<sup>3</sup> DNEL (Consumer; oral, long term systemic effects): 699 mg/kg bw/day DNEL (Industry; dermal, long term systemic effects): 773 mg/kg bw/day DNEL (Industry; inhalational, long term systemic effects): 2035 mg/m<sup>3</sup>

propan-2-ol; isopropyl alcohol; isopropanol

WEL (short term): 500 ppm 1250 mg/m<sup>3</sup>

WEL (long term): 400 ppm 999 mg/m<sup>3</sup> (8 hour TWA)

DNEL (Consumer; dermal, long term systemic effects): 888 mg/kg DNEL (Consumer; inhalational, long term systemic effects): 500 mg/m³

DNEL (Consumer; oral, long term systemic effects): 26 mg/kg

Datasheet Number: 03002 - v3.0.0

Created: 20 Sep 2024. Revised:: 20 Sep 2024.

## **SECTION 8:** Exposure controls/personal protection (....)

DNEL (Industry; dermal, long term systemic effects): 319 mg/kg DNEL (Industry; inhalational, long term systemic effects): 89 mg/m³

PNEC:

PNEC (Fresh water): 140.9 mg/l
PNEC (Marine water): 140.9 mg/l
PNEC (Sediment; fresh water): 552 mg/kg
PNEC (Sediment; marine water): 552 mg/kg
PNEC (Soil): 28 mg/kg
PNEC (STP): 2251 mg/l

Petroleum gases, liquefied

WEL (short term): 1250 ppm 2180 mg/m<sup>3</sup>

WEL (long term): 1000 ppm 1750 mg/m<sup>3</sup> (8 hour TWA)

8.2 Exposure controls





- Wear goggles giving complete eye protection
- BS EN PPE Codes: EN 166:2001
- Wear butyl rubber gloves
- In case of insufficient ventilation, wear suitable respiratory equipment
- Where an air-purifying respirator is suitable, use EN141 or EN405, type A

# **SECTION 9: Physical and chemical properties**

9.1 Information on basic physical and chemical properties

- Physical state: Aerosol

Colour: Colourless to yellowOdour: Characteristic odourOdour threshold: Not available

Melting point/Range: Not applicableBoiling Point/Range: Not applicable

- Flammability: H222 - Extremely flammable aerosol.

- Explosive Properties: H229 - Pressurised container: May burst if heated.

Lower Explosive Limit: Not available
 Upper Explosive Limit: Not available
 pH: Not applicable
 Solubility in water: Not available
 Relative density: 0.68 typical

Flash point - not applicableVapour pressure - not known

- Partition coefficient : n-Octanol/water - not known

- Viscosity - not applicable

- Evaporation rate - not applicable

- Decomposition temperature: Not applicable

9.2 Other information

- Volatile Organic Compound Content ca. 100%

### SECTION 10: Stability and reactivity

10.1 Reactivity

Datasheet Number: 03002 - v3.0.0

Created: 20 Sep 2024. Revised:: 20 Sep 2024.

# **SECTION 10:** Stability and reactivity (....)

- Extremely flammable aerosol.
- Pressurised container: May burst if heated.
- 10.2 Chemical stability
  - Considered stable under normal conditions
- 10.3 Possibility of hazardous reactions
  - No hazardous reactions known if used for its intended purpose
- 10.4 Conditions to avoid
  - Keep away from heat
  - Keep away from naked flames, incandescent or hot surfaces
- 10.5 Incompatible materials
  - Avoid contact with oxidising substances
- 10.6 Hazardous decomposition products
  - Decomposition products may include carbon oxides

# **SECTION 11:** Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

```
Acute toxicity
```

```
Estimated LD<sub>50</sub> (oral) (ATE) : >2000 \text{ mg/kg}
Estimated LD<sub>50</sub> (dermal) (ATE) : >4000 \text{ mg/kg}
```

Estimated LD50 (inhalational) (ATE): >20 mg/l/4hr (gas/vapour)

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

LC50 (inhalation, rat): 73680 ppm LD50 (oral, rat): 5840 mg/kg LD50 (skin, rabbit): 3160 mg/kg LD50 (skin, rat): 2920 mg/kg

propan-2-ol; isopropyl alcohol; isopropanol

LDso (dermal, rabbit): 12800 mg/kg LDso (oral, rat): 5840 mg/kg LCso (inhalation, rat): 10000 ppm

Petroleum gases, liquefied

LC50 (inhalation, rat): >20 mg/l (4 hr)

Skin corrosion/irritation

propan-2-ol

Causes skin irritation.

pH: 7

Serious eye damage/irritation

Causes serious eye irritation.

pH: 7

Respiratory or skin sensitisation

Based on the available data, the classification criteria are not met

Germ cell mutagenicity

Based on the available data, the classification criteria are not met

Datasheet Number: 03002 - v3.0.0

Created: 20 Sep 2024. Revised:: 20 Sep 2024.

## **SECTION 11:** Toxicological information (....)

Carcinogenicity

Based on the available data, the classification criteria are not met

Reproductive toxicity

Based on the available data, the classification criteria are not met

STOT (specific target organ toxicity) - single exposure

Vapours may cause drowsiness and dizziness

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

May cause drowsiness or dizziness.

Hydrocarbons, C6, Isoalkanes, <5% N-Hexane

Vapours may cause drowsiness and dizziness

propan-2-ol

Vapours may cause drowsiness and dizziness

STOT (specific target organ toxicity) - repeated exposure

Based on the available data, the classification criteria are not met

Aspiration hazard

May be fatal if swallowed and enters airways.

Calculation method

11.2 Information on other hazards

- Not available

# **SECTION 12:** Ecological information

## 12.1 Toxicity

```
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane
```

EC<sub>50</sub> (daphnia): 3 mg/l (48 hr) LC<sub>50</sub> (fish): 11.4 mg/l (96 hr)

propan-2-ol; isopropyl alcohol; isopropanol

IC<sub>50</sub> (algae): >100 mg/l (72 hr) EC<sub>50</sub> (daphnia): >100 mg/l (48 hr) LC<sub>50</sub> (fish): >100 mg/l (96 hr)

Petroleum gases, liquefied

IC<sub>50</sub> (algae): >100 mg/l (72 hr) EC<sub>50</sub> (daphnia): >100 mg/l (48 hr) LC<sub>50</sub> (fish): >100 mg/l (96 hr)

Hydrocarbons, C6, Isoalkanes, <5% N-Hexane

IC<sub>50</sub> (algae): Unknown mg/l (72 hr) EC<sub>50</sub> (daphnia): 3 mg/l (48 hr)

LC<sub>50</sub> (fish): 12 mg/l (96 hr)

(R)-p-mentha-1,8-diene; d-limonene

IC<sub>50</sub> (algae): .3 mg/l (72 hr) EC<sub>50</sub> (daphnia): .5 mg/l (48 hr) LC<sub>50</sub> (fish): 0.7 mg/l (96 hr)

12.2 Persistence and degradability

Datasheet Number: 03002 - v3.0.0

Created: 20 Sep 2024. Revised:: 20 Sep 2024.

## **SECTION 12:** Ecological information (....)

- Not readily biodegradable

Petroleum gases, liquefied

Not readily biodegradable

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Not readily biodegradable

Hydrocarbons, C6, Isoalkanes, <5% N-Hexane

Not readily biodegradable

propan-2-ol

Not readily biodegradable

(R)-p-mentha-1,8-diene; d-limonene

Not readily biodegradable

12.3 Bioaccumulative potential

propan-2-ol; isopropyl alcohol; isopropanol

Partition coefficient: n-Octanol/water 0.05 OECD 107

- 12.4 Mobility in soil
  - No information available
- 12.5 Results of PBT and vPvB assessment
  - Not a PBT according to REACH Annex XIII
- 12.6 Endocrine disrupting properties
  - The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Common Delegated Regulation (EU) 2017/2010 or Common Regulation (EU) 2018/605 at a concentration equal or greater than 0.1%.
- 12.7 Other adverse effects
  - Do not discharge into drains or the environment, dispose to an authorised waste collection point

# **SECTION 13: Disposal considerations**

- 13.1 Waste treatment methods
  - Dispose of contents/container to an authorised waste collection point
  - EU Waste Codes: 160504. 150104, 150110

# **SECTION 14: Transport information**





14.1 UN number or ID number

- UN No.: 1950

14.2 UN proper shipping name

- Proper Shipping Name: AEROSOLS

14.3 Transport hazard class(es)

- Hazard Class: 2.1

Datasheet Number: 03002 - v3.0.0

Created: 20 Sep 2024. Revised:: 20 Sep 2024.

# SECTION 14: Transport information (....)

#### 14.4 Packing group

- Packing Group: Not applicable

#### 14.5 Environmental hazards

- Marine Pollutant
- Environmentally hazardous

#### 14.6 Special precautions for user

- ADR/RID special provisions 190, 327, 344, 625

Tunnel Code: DLimited quantity (LQ): 1 Ltr

#### 14.7 Maritime transport in bulk according to IMO instruments

- Not applicable

# **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- The Health and Safety at Work Act applies in the UK
- The COSHH Regulations apply in the UK
- The Hazardous Waste (England and Wales) Regulations 2005 apply in the UK
- The Workplace Directive (89/654/EEC) applies in the UK
- The CLP Regulations apply in the UK
- Where UK Regulations are quoted, then for other nations the equivalent regulations should be identified
- Water Hazard Class (Company): 3
- Refer to current ADR Regulations
- Refer to current EC Directive 2012/18/EU (the Seveso III Directive)
- Volatile Organic Compound Content ca. 100%

#### 15.2 Chemical safety assessment

- A chemical safety assessment (CSA) for this product has not yet been completed
- This Safety Data Sheet does not constitute a workplace risk assessment

## SECTION 16: Other information

Text not given with phrase codes where they are used elsewhere in this safety data sheet:- H220: Extremely flammable gas. H225: Highly flammable liquid and vapour. H226: Flammable liquid and vapour. H280: Contains gas under pressure; may explode if heated. H304: May be fatal if swallowed and enters airways. H315: Causes skin irritation. H317: May cause an allergic skin reaction. H319: Causes serious eye irritation. H336: May cause drowsiness or dizziness. H400: Very toxic to aquatic life. H410: Very toxic to aquatic life with long lasting effects.

#### Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses parRoute

RID = Règlement concernant le transport international ferroviaire de marchandisesdangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses parvoie de navigation intérieure

ATE = acute toxicity estimate

CAS = Chemical Abstracts Service

CLP = Classification, Labelling and Packaging

DMEL = Derived Minimum Effect Level

DNEL = Derived No Effect Level

EC50 = Median effective concentration

ECB = European Chemicals Bureau

EEC = European Economic Community

EINECS = European Inventory of Existing Commercial Chemical Substances

ELINCS = European List of Notified Chemical Substances

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC-Code = International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk

IC50 = Inhibition concentration, 50%

IMDG = International Maritime Code for Dangerous Goods

IUCLID = International Uniform Chemical Information Database

LC50 = Lethal concentration, 50%

Datasheet Number: 03002 - v3.0.0

Created: 20 Sep 2024. Revised:: 20 Sep 2024.

## **SECTION 16:** Other information (....)

LD50 = Median lethal dose

LC0 = lethal concentration, 0%

LOAEL = lowest-observed-adverse-effect level

MARPOL = International Convention for the Prevention of Marine Pollution from Ships

NOAEL = No Observed Adverse Effect Level NOEC = No Observed Effect Concentration

PBT = Persistent, Bioaccumulative and Toxic substance

PNEC = Predicted No-Effect Concentration

REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals

STP = Sewage Treatment Plant

$$\label{eq:thm_state} \begin{split} &\text{TLV}_{\text{\ensuremath{\$}}}/\text{TWA} = \text{Threshold limit value} - \text{time-weighted average} \\ &\text{TLV}_{\text{\ensuremath{\$}}}\text{STEL} = \text{Threshold limit value} - \text{short-time exposure limit} \end{split}$$

VOC = Volatile Organic Compounds

vPvB = very Persistent and very Bioaccumulative

Changes made: See Section 2

Removed: H410 - Very toxic to aquatic life with long lasting effects.

Added: H411 - Toxic to aquatic life with long lasting effects.

Changes made: See Section 3 Removed: N-heptane

Added: Hydrocarbons C6-7; Hydrocarbons C6; d-Limonene

Due to major changes made, this Safety Data Sheet should be read entirely as new.

Use good personal hygiene practices

Do not mix with any other products

#### Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any othermaterials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the dateindicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy themselvesf as to the suitability of such information for their own particular use.

Datasheet Number: 03002 - v3.0.0

Created: 20 Sep 2024. Revised:: 20 Sep 2024.